COMMANDER GRAND TOURER 2019



Commander Grand Tourer 1200 4-TEC

ROTAX° ENGINE	<i>900 ACE</i>	1200 4-TEC
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3	3
Displacement	899.0 cc	1170.7 cc
Bore	74 mm	91 mm
Stroke	69.7 mm	60 mm
Maximum engine speed	7250 RPM	7800 RPM
Carburation	EFI	EFI
Recommended fuel type	Regular unleaded	Regular unleaded
Minimum octane	95	95
Fuel tank	40 liters	40 liters

POWERTRAIN

Drive clutch type	eDrive II	
Driven clutch type	QRS SS	
Small sprocket number of teeth	1st gear = 3.23:1 ratio	
Large sprocket number of teeth	2nd gear = 1.98:1 ratio	
Drive sprocket	8	
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder	

Black/Race Orange

DIMENSIONS

Vehicle overall length	3260 mm	
Vehicle overall width	1180 mm	
Vehicle overall height	1445 mm	
Ski stance	996 +/- 21 mm	
Track nominal width	500 mm	
Track nominal length	3923 mm	
Track profile height	38 mm	

SUSPENSION

Front suspension	A-LFS+ with bended lower A-Arms	
Front shock	HPG 36	
Rear suspension	PPS-5900-A	
Center shock	HPG 36	
Rear shock	HPG 36	

FEATURES

L-XU	
Blade XC	
Luxury Modular 1+1 (heated rider seat)	
U-type steel	
Adjustable 130-205 mm	
Electric	
Mechanical (2F-N-R)	
Standard	

Heated grips	Standard	
Gauge	Multifunction	
Mirrors	Standard	
Windshield	High (510 mm), one piece	
Hitch	Standard	
Visor Plug front / rear	Front	
12V power outlet	Front	

LYNX.

©2018 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, ® and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.