

Commander LTD 900 ACE

ROTAX" ENGINE	600 E-TEC	<i>900 ACE</i>
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	594.4 cc	899.0 cc
Bore	72 mm	74 mm
Stroke	73 mm	69.7 mm
Maximum engine speed	8100 RPM	7250 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Premium unleaded	Regular unleaded
Minimum octane	95	95
Fuel tank	40 liters	40 liters
Oil tank capacity (2-stroke)	2,9 liters	-

POWERTRAIN

Drive clutch type	TRA 3	eDrive II
Driven clutch type	QRS SS	
Small sprocket number of teeth	1st gear = 3.23:1 ratio	
Large sprocket number of teeth	2nd gear = 1.98:1 ratio	
Drive sprocket	7	
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder	

FEATURES

Frame	L-XU	
Skis	Blade XC	
Seating	Modular, 1+1 (heated rider seat)	
Handlebar	U-type steel, mountain strap	
Riser block height	130 mm	
Starter	Manual, Electric	
Reverse	Mechanical (2F-N-R)	
Heated throttle lever	Standard	

COLOUR Black/Race Orange

DIMENSIONS

Vehicle overall length	3260 mm	
Vehicle overall width	1180 mm	
Vehicle overall height	1445 mm	
Ski stance	996 +/- 21 mm	
Track nominal width	500 mm	
Track nominal length	3923 mm	
Track profile height	44 mm	

SUSPENSION

Front suspension	A-LFS+ with bended lower A-Arms	
Front shock	HPG 36	
Rear suspension	EasyRide	
Center shock	HPG 36	
Rear shock	HPG 36	

Heated grips	Standard	
Gauge	Multifunction	
Mirrors	Accessory	
Windshield	High (510 mm), one piece	
Hitch	Standard	
Visor Plug front / rear	Front	
12V power outlet	Front	

©2018 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, ® and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

