

| <i>ROTAX" ENGINE</i> | 850 E-TEC |
|------------------------------|---|
| Engine details | Liquid-cooled, 3-D R.A.V.E.™ |
| Cylinders | 2 |
| Displacement | 849 cc |
| Bore | 82 mm |
| Stroke | 80.4 mm |
| Maximum engine speed | 7900 RPM |
| Carburation | Electronic Direct Injection with additional booster injectors |
| Recommended fuel type | Premium unleaded |
| Minimum octane | 95 |
| Fuel tank | 37 liters |
| Oil tank capacity (2-stroke) | 3.4 liters |

| Engine details | Liquid-cooled, 5-D R.A.V.E |
|------------------------------|---|
| Cylinders | 2 |
| Displacement | 849 cc |
| Bore | 82 mm |
| Stroke | 80.4 mm |
| Maximum engine speed | 7900 RPM |
| Carburation | Electronic Direct Injection with additional booster injectors |
| Recommended fuel type | Premium unleaded |
| Minimum octane | 95 |
| Fuel tank | 37 liters |
| Oil tank capacity (2-stroke) | 3,4 liters |

| POWERTRAIN | |
|--------------------------------|---------------------|
| Drive clutch type | pDrive with clicker |
| Driven clutch type | QRS |
| Small sprocket number of teeth | |
| Large sprocket number of teeth | |
| Drive sprocket | |

Hydraulic brake with braided steel brake Brake system line, plastic master cylinder

COLOUR



DIMENSIONS

| Vehicle overall length | 3150 mm |
|------------------------|--------------------------|
| Vehicle overall width | 1180 mm |
| Vehicle overall height | 1230 mm |
| Ski stance | 996 +/- 21 mm |
| Track nominal width | 406 mm |
| Track nominal length | 3705 mm |
| Track profile height | 51 mm PowderMax FlexEdge |
| | |

SUSPENSION

| Front suspension | LFS |
|------------------|------------------------|
| Front shock | KYB 40 HLCR Kashima |
| Rear suspension | PPS ² -3700 |
| Center shock | KYB 46 HLCR Kashima |
| Rear shock | KYB 46 HLCR Kashima |

FEATURES

| Frame | Radien |
|-----------------------|-----------------------------|
| Skis | Blade XC |
| Seating | Crossover, 1-up |
| Handlebar | U-type aluminium with hooks |
| Riser block height | 120 mm |
| Starter | Manual, Electric |
| Reverse | RER |
| Heated throttle lever | Standard |

| Gauge Multifunction Mirrors - Windshield Low / 360 mm Hitch Accessory Visor Plug front / rear Front 12V power outlet Yes, in glove box | Heated grips | Standard |
|--|-------------------------|-------------------|
| Windshield Low / 360 mm Hitch Accessory Visor Plug front / rear Front | Gauge | Multifunction |
| Hitch Accessory Visor Plug front / rear Front | Mirrors | - |
| Visor Plug front / rear Front | Windshield | Low / 360 mm |
| | Hitch | Accessory |
| 12V power outlet Yes in glove hox | Visor Plug front / rear | Front |
| Tee, iii Bieve sex | 12V power outlet | Yes, in glove box |







ROTAX® ENGINE 850 E-TEC Engine details Liquid-cooled, 3-D R.A.V.E.™ 2 Cylinders Displacement 849 cc Bore 82 mm 80.4 mm Stroke 7900 RPM Maximum engine speed Electronic Direct Injection with additional Carburation booster injectors Recommended fuel type Premium unleaded Minimum octane 37 liters Fuel tank 3,4 liters Oil tank capacity (2-stroke)

DIMENSIONS

COLOUR

| Vehicle overall length | 3150 mm |
|------------------------|--------------------------|
| Vehicle overall width | 1180 mm |
| Vehicle overall height | 1230 mm |
| Ski stance | 996 +/- 21 mm |
| Track nominal width | 406 mm |
| Track nominal length | 3923 mm |
| Track profile height | 51 mm PowderMax FlexEdge |

Black/White

POWERTRAIN

| Drive clutch type | pDrive with clicker |
|--------------------------------|--|
| Driven clutch type | QRS |
| Small sprocket number of teeth | |
| Large sprocket number of teeth | |
| Drive sprocket | |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder |

SUSPENSION

| Front suspension | LFS |
|------------------|------------------------|
| Front shock | KYB 40 HLCR Kashima |
| Rear suspension | PPS ² -3900 |
| Center shock | KYB 46 HLCR Kashima |
| Rear shock | KYB 46 HLCR Kashima |

FEATURES

| Frame | Radien |
|-----------------------|-----------------------------|
| Skis | Blade XC |
| Seating | Crossover, 1-up |
| Handlebar | U-type aluminium with hooks |
| Riser block height | 120 mm |
| Starter | Manual, Electric |
| Reverse | RER |
| Heated throttle lever | Standard |

| Heated grips | Standard |
|-------------------------|-------------------|
| Gauge | Multifunction |
| Mirrors | - |
| Windshield | Low / 360 mm |
| Hitch | Accessory |
| Visor Plug front / rear | Front |
| 12V power outlet | Yes, in glove box |
| | |



