

FOR 60 YEARS, WE'VE SEEN WHAT KIND OF TROUBLE YOU CAN GET INTO ON A FRESH BED OF SNOW. TRAILS THAT BEG YOU TO OPEN THE THROTTLE. MOUNTAINS TO TAME. ADVENTURES TO LAST A LIFETIME. THEY'RE THE JOURNEYS EVERY ARCTIC CAT IS BUILT FOR. WE'VE BEEN RAISING HELL AND RAISING THE BAR SINCE 1962. NOW IT'S YOUR TURN.



A NEW ERA OF







WITH ELECTRONIC POWER STEERING

The world's fastest production snowmobile gets unprecedented handling, for more control on every thrill ride.



RIOT X WITH ATAC[™] A CROSSOVER WITH ADJUSTABLE ON-THE-FLY SUSPENSION

How do you make a true 50/50 crossover snowmobile even more versatile? With shocks that adapt as quickly as the terrain changes, at the push of a button.



BLAST XR + BLAST XR TOURING

DOUBLE FUN

BLAST is back with two new ways to double down on fun. The BLAST XR crossover takes adventure anywhere, and the two-seater BLAST XR Touring lets you bring another trouble maker along for the ride.





THE TECH NO OTHER RIDE CAN TOUCH.

Making trouble means making your own way. Nobody else builds a single-beam rear suspension, shocks that change on the fly, or a CVT like this. Because nobody else is Arctic Cat.





ELECTRONIC POWER STEERING

Know what the world's most powerful production snowmobile needs? A new kind of power. We're unleashing Electronic Power Steering on the ZR® 9000 Thundercat. Speed freaks and control freaks, unite!



ADJUSTABLE ON-THE-FLY SUSPENSION

The terrain can change quickly. Now you can be ready for whatever comes at you with ATAC[™] Adjustable On-the-Fly Suspension. With the push-button command of three firmness settings, lockout mode and two individual rider profiles, you'll always ride on your terms.

AVAILABLE ON: MOUNTAIN CAT ALPHA ONE, RIOT X, ZR 9000 THUNDERCAT EPS

ATAC's FOX[®] ZERO iQS shocks feature piggyback reservoirs, three compression settings (Soft, Medium and Firm) and two custom rider profiles.



Dual LED screens and handlebar-mounted controls make it easy to adjust suspension in seconds.



CONTINUOUSLY VARIABLE TRANSMISSION

Bring new life to every ride, with a new transmission that delivers




more consistent performance, longer belt life and less maintenance.

AVAILABLE ON: EVERY Full-sized 2022 Arctic Cat

SINGLE-BEAM REAR SUSPENSION

ALPHA ONE[™] unlocks the mountain with the revolutionary single-beam design for incredible maneuverability. With minimal input, you get effortless deep-snow cornering, carving, side-hilling and more. You've never felt a ride like this.

AVAILABLE ON: MOUNTAIN CAT ALPHA ONE, Hardcore Alpha one, riot X, blast M



Instead of using a traditional dual-rail suspension, ALPHA ONE has a single aluminum rail that runs right down the center of the track, delivering agility that dual-rail sleds can't match. The single-beam design of ALPHA ONE eliminates almost all snow accumulation that weighs you down.

SPECS



BLAST is the right size for your next adventure: bigger than our ZR 200 youth sleds, and more nimble than a full-sized sled.

Armed with a powerful, industry-first engine and a best-in-class power-to-weight ratio, the new BLAST Series packs jaw-dropping features. That means faster turns, easier rides and fewer compromises. 400 SINGLE-CYLINDER 2-STROKE EFI ENGINE LIGHTWEIGHT CHASSIS UNRIVALED SUSPENSION TECHNOLOGY TURN-KEY ELECTRIC START

~ ~ ~



BLAST XR NEW FOR 2022

Take BLAST on the trail or maneuver through the backcountry.

- > SLIDE-RAIL REAR SUSPENSION
- > DUAL-SHOCK AND ADJUSTABLE TORSION SPRINGS
- > ARCTIC MOUNTAIN FRONT SUSPENSION (AMS)
- > TURN-KEY ELECTRIC START



BLAST XR TOURING NEW FOR 2022

Double the fun on BLAST XR Touring, a two-seater built on the BLAST frame.

- > 2-UP SEAT
- > SLIDE-RAIL REAR SUSPENSION
- > DUAL-SHOCK, ADJUSTABLE TORSION SPRINGS AND OVERLOAD SPRINGS
- > TURN-KEY ELECTRIC START



BLAST M WITH ALPHA ONE™

Loaded with the agility of ALPHA ONE, the BLAST M is putting higher altitudes on notice.

- > ALPHA ONE SINGLE-BEAM REAR SUSPENSION
- > ARCTIC MOUNTAIN FRONT SUSPENSION
- > CHALLENGER TRACK
- > LIGHTWEIGHT ONE-PIECE TUNNEL
- > TURN-KEY ELECTRIC START



100

BLAST ZR[®]

Born with the bloodline of racing champions, the BLAST ZR trail sled is ready to defy a few expectations.

- > SLIDE-RAIL REAR SUSPENSION
- > TRAIL 6 SKI

1000

- > LIGHTWEIGHT ONE-PIECE TUNNEL
- > TURN-KEY ELECTRIC START



BLAST LT

Handle every job on your terms, or just cut loose on the trails. The BLAST LT sport utility sled is designed to let you work hard and play even harder.

- > XTRA-ACTION REAR SUSPENSION
- > STANDARD TUNNEL RACK
- > HIGH WINDSHIELD & RAISED SEAT
- > TURN-KEY ELECTRIC START

000

SPECS

07

XTRA-ACTION

ECHNOLOGY

BLAST

Adjust to any terrain from the trail to the backcountry, with available ATAC[™] Adjustable On-the-Fly Suspension. And for mountain supremacy, RIOT X packs an ALPHA ONE[™] Single-Beam Rear Suspension.

 \land \land \land \land \land

~ ~ ~ ~ ~ ~ ~ ~

 \wedge \wedge \wedge





Our new Continuously Variable Transmission delivers better performance and longer belt life.

RIOT X 8000

- > NEXT GENERATION 800 C-TEC2[™] 165HP-CLASS ENGINE
- > ALPHA ONE SINGLE-BEAM REAR SUSPENSION
- > AVAILABLE ATAC[™] ADJUSTABLE ON-THE-FLY SUSPENSION WITH LOCKOUT MODE
- > ATAC FEATURES FOX 1.5 ZERO IQS SKI SHOCKS AND REAR TRACK SHOCK
- > ARCTIC MOUNTAIN FRONT SUSPENSION
- > AVAILABLE FOX" 1.5 ZERO QS3 SKI AND TRACK SHOCKS
- > PROCLIMB[™]-7 G2 MOUNTAIN SKIS
- > 2.6" POWER CLAW™ TRACK > PUSH-BUTTON ELECTRIC START

The single-beam design of ALPHA ONE delivers drastically improved maneuverability while eliminating snow pack that can weigh you down.



Adjust your suspension settings instantly to get more from every second of your ride.



RIOT 8000

- > NEXT GENERATION 800 C-TEC2 165HP-CLASS ENGINE
- > ARS[™] II FRONT SUSPENSION
- > AVAILABLE FOX 1.5 ZERO QS3 SKI SHOCKS AND FOX 2.0 ZERO QS3 REAR TRACK SHOCK
- > LIGHTWEIGHT CROSS-ACTION REAR SUSPENSION

> PROCLIMB-7 G2 MOUNTAIN SKIS

> PUSH-BUTTON ELECTRIC START

SPECS

09

.

No. CAR

On the mountain, control is king. Which is why up here, Arctic Cat reigns, with a revolutionary ALPHA ONE[™] Single-Beam Rear Suspension on every mountain sled. For even greater control, step up to ATAC[™] Adjustable On-The-Fly Suspension.



M 8000 MOUNTAIN CAT ALPHA ONE/TWINRAIL

- > NEXT GENERATION 800 C-TEC2[™] 165HP-CLASS ENGINE
- > AVAILABLE ATAC ADJUSTABLE ON-THE-FLY SUSPENSION WITH LOCKOUT MODE
- > ATAC FEATURES FOX® FLOAT 3 IQS SKI SHOCKS AND REAR TRACK SHOCK
- > AVAILABLE WITH FOX FLOAT QS3 SKI AND TRACK SHOCKS
- > ASCENDER PLATFORM > 2.6" POWER CLAW™ TRACK
- > AVAILABLE IN 154" TRACK LENGTH
- > PUSH-BUTTON ELECTRIC START



M 8000 HARDCORE ALPHA ONE

- > NEXT GENERATION 800 C-TEC2 165HP-CLASS ENGINE
- > FOX 1.5 ZERO QS3 SKI AND TRACK SHOCKS
- > ASCENDER PLATFORM
- > REINFORCED RUNNINGBOARDS AND TWO-PIECE TUNNEL
- > 3" POWER CLAW TRACK
- > AVAILABLE IN 146", 154" OR 165" TRACK LENGTHS

North

The only single-beam rear suspension on the mountain lets you side-hill, carve through deep powder and own the backcountry.

SPECS

[R A I I

TRAIL

ZR

We've never been afraid to blaze a trail. So this year, we're giving the world's fastest production snowmobile Electronic Power Steering, making the ZR 9000 Thundercat the unquestioned pack leader. We were born on the trails, and born to make trouble.



ZR 9000 THUNDERCAT®

- > 200+ HP-CLASS 998cc TURBO ENGINE
- > AVAILABLE (EPS) ELECTRONIC POWER STEERING
- > AVAILABLE ATAC ADJUSTABLE ON-THE-FLY SUSPENSION
- > ATAC FEATURES 1.5 ZERO IQS SKI SHOCK AND 2.0 ZERO IQS REAR TRACK SHOCK
- > ARS[™] II FRONT SUSPENSION
- > SLIDE-ACTION REAR SUSPENSION™
 - > PUSH-BUTTON ELECTRIC START



The world's fastest production snowmobile just got more untouchable. **Electronic Power Steering** makes this the most agile Thundercat yet.

ELECTRONIC -









ZR 8000 RR

- > NEXT GENERATION 800 C-TEC2 165HP-CLASS ENGINE
- > ARS II FRONT SUSPENSION
- > SLIDE-ACTION REAR SUSPENSION
- > KASHIMA-COATED FOX 1.5 ZERO QS3R SKI SHOCKS
- > KASHIMA-COATED FOX 1.5 ZERO QS3 FRONT TRACK SHOCK
- > KASHIMA-COATED FOX 2.0 ZERO QS3R REAR TRACK SHOCK
- > PUSH-BUTTON ELECTRIC START

13

TRAIL

8

5-63

10.00

1

-

1002

PL PAR



There's work to be done. And when the job is over, it's time to cut loose. That's what this work-hard, play-hard vehicle is all about. It's loaded with productivity-focused features that give this trusted Arctic Cat snowmobile an extra load of work ethic.



XTRAACTION

ADAPT

8.8

1942

1223

NORSEMAN X 8000

- > NEXT GENERATION 800 C-TEC2™ 165HP-CLASS ENGINE
- > XTRA-ACTION REAR SUSPENSION
- > PAINTED CHASSIS
- > PUSH-BUTTON ELECTRIC START



Let's start the next generation of riders early with easy-to-handle snowmobiles that make them fall in love with riding with every new trail they blaze. These sleds are built for young riders.



ZR° 200

- > 192cc 4-STROKE ENGINE
- > SSCC TRAIL-CERTIFIED
- > LIGHT-WEIGHT REAR SUSPENSION RAILS
- > 5-WAY ADJUSTABLE SHOCKS (FRONT AND REAR)
- > PAINTED CHASSIS
- > TURN-KEY ELECTRIC START

2022 LINEUP









	NEW	NEW		
	BLAST XR	BLAST XR TOURING	BLAST M	BLAST LT
KEY TECHNOLOGIES (*Optional)			ALPHA-ONE	
COLOR OPTIONS				
STANDARD COLORS	Dynamic Charcoal/Gold	Dynamic Charcoal/Gold	Dynamic Charcoal/Fire Red, Dynamic Charcoal/Orange	Dynamic Charcaol/Fire Red
ENGINE				
ENGINE / TYPE / DISPLACEMENT / COOLING / CYLINDERS	4000 Series / 2-Stroke / 397cc / Liquid / 1 Cylinder	4000 Series / 2-Stroke / 397cc / Liquid / 1 Cylinder	4000 Series / 2-Stroke / 397cc / Liquid / 1 Cylinder	4000 Series / 2-Stroke / 397cc / Liquid / 1 Cylinder
FUEL CAPACITY / OIL SYSTEM CAPACITY	44.3 l (11.7 gal) / 3.08 l (3.25 qt)	44.3 l (11.7 gal) / 3.08 l (3.25 qt)	44.3 l (11.7 gal) / 3.08 l (3.25 qt)	44.3 l (11.7 gal) / 3.08 l (3.25 qt)
DRIVE CLUTCH	CVTech Trailbloc	CVTech Trailbloc	CVTech Trailbloc	CVTech Trailbloc
DRIVEN CLUTCH	CVTech Invance	CVTech Invance	CVTech Invance	CVTech Invance
SUSPENSION				
FRONT SUSPENSION	Arctic Mountain Suspension (AMS)	Arctic Mountain Suspension (AMS)	Arctic Mountain Suspension (AMS)	Arctic Mountain Suspension (AMS)
REAR SUSPENSION	Slide-Rail, Dual Shock and Adjustable Torsion Springs	Slide-Rail, Dual Shock, Adjustable Torsion Springs and Overload Springs	ALPHA-ONE Rear Suspension	XTRA-ACTION Rear Suspension with Dual Shocks and Adjustable Torsion Springs
SKI SHOCKS	Hydraulic Twin Tube	Hydraulic Twin Tube	Hydraulic Twin Tube	Hydraulic Twin Tube
FRONT TRACK SHOCK	Hydraulic Twin Tube	Hydraulic Twin Tube	Hydraulic Twin Tube	Hydraulic Twin Tube
REAR TRACK SHOCK	Hydraulic Twin Tube	Hydraulic Twin Tube	Hydraulic Twin Tube	Hydraulic Twin Tube
CHASSIS & TRACK				
CHASSIS OVERALL LENGTH / WIDTH / HEIGHT	325 cm / 112-114 cm / 128.3 cm (128 in. / 44-45 in. / 50.5 in.)	325 cm / 117-118.5 / 128.3 (128 in. / 46-47 in. / 50.5 in.)	325 cm / 112-117 cm / 97.8 cm (128 in. / 44-46 in. / 38.5 in.)	325 cm/112-114 cm/128.3 cm (128 in. / 44-45 in. / 50.5 in.)
TRACK TYPE	Cobra	Ripsaw	Challenger	Cobra
TRACK WIDTH / LENGTH / LUG	38 cm / 371 cm / 4.1 cm (15 in. / 146 in. / 1.60 in.)	38 cm / 371 cm / 3.2 cm 15 in. / 146 in. / 1.25 in.	38 cm / 371 cm / 5.1 cm (15 in. / 146 in. / 2 in.)	38 cm / 371 cm / 4.1 cm (15 in. / 146 in. / 1.60 in.)
SKI STANCE	95-98 cm (37.5-38.5 in.) Adjustable	100-103 cm (39.5-40.5 in.) Adjustable	94-99 cm (37-39) in. Adjustable	95-98 cm (37.5-38.5 in.) Adjustable
FEATURES				
STARTER	Turn-key Electric Start	Turn-key Electric Start	Turn-key Electric Start	Turn-key Electric Start
HEADLIGHTS	Halogen 1-Bulb	Halogen 1-Bulb	Halogen 1-Bulb	Halogen 1-Bulb
WINDSHIELD	10.2 cm (4 in.) Low-Height	39.4 cm (15.5 in.) High-Height	10.2 cm (4 in.) Low-Height	39.4 cm (15.5 in.) High-Height
STANDARD FEATURES	Hand and Thumb Warmers, Tether Switch, Digital Gauge	Hand and Thumb Warmers, Tether Switch, Digital Gauge	Hand and Thumb Warmers, Tether Switch, Digital Gauge	Hand and Thumb Warmer, Rear Rack, Tether Switch, Digital Gauge







BLAST ZR	M 8000 MOUNTAIN CAT Alpha one/twinrail	M 8000 HARDCORE ALPHA ONE	
	ALPHA-ONE, ATAC, ADAPT	ALPHA-ONE, ADAPT	
Dynamic Charcoal/Medium Green, Dynamic Charcoal/Skye Blue	Dynamic Charcoal/Skye Blue	Orange/Black, Medium Green/Black	
4000 Series / 2-Stroke / 397cc / Liquid / 1 Cylinder	8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder	8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder	
44.3 l (11.7 gal) / 3.08 l (3.25 qt)	44.3 l / 3.08 l (11.7 gal / 3.25 qt)	39.4 l / 3.08 l (10.4 / 3.25 qt)	
CVTech Trailbloc	ADAPT CVT	ADAPT CVT	
CVTech Invance	ADAPT CVT	ADAPT CVT	
Arctic Mountain Suspension (AMS)	Arctic Mountain Suspension (AMS)	Arctic Mountain Suspension (AMS)	
Slide-Rail, Dual Shock and Adjustable Torsion Springs	ALPHA-ONE Rear Suspension	ALPHA-ONE Rear Suspension	
Hydraulic Twin Tube	FOX FLOAT 3 QS3 or FOX FLOAT 3 iQS	FOX 1.5 ZERO QS3 COIL-OVER	
Hydraulic Twin Tube	FOX FLOAT 3 QS3 or Arctic Cat IFP 1.5	FOX 1.5 ZERO QS3 COIL-OVER	
Hydraulic Twin Tube	FOX FLOAT 3 QSL or FOX FLOAT 3 iQSL	FOX 1.5 ZERO QSL COIL-OVER	
292 cm / 112-114 cm / 96.5 cm (115 in. / 44-45 in. / 38 in.)	335 cm / 108-113 cm / 127 cm (132 in. / 42.5-44.5 in. / 50 in.)	333 cm or 335 or 348 cm / 108-113 cm / 127 cm (131 in. or 132 in. or 137 in. / 42.5-44.5 in. / 50 in.)	
Standard	Power Claw	Power Claw	
35.5 cm / 308 cm / 2.5 cm (14 in. / 121 in. / 1 in.)	38 cm / 389 or 391 cm / 6.6 cm (15 in. / 154 or 153 in. / 2.6 in.)	38 cm / 371 cm or 391 cm or 419 cm / 6.6 or 7.6 cm (15 in. / 146 or 154 or 165 in. / 2.6 or 3 in.)	
95-98 cm (37.7-38.5 in.) Adjustable	90-96 cm (35.5-37.5 in.) Adjustable	90-96 cm (35.5-37.5 in.) Adjustable	
Turn-key Electric Start	Push-Button Electric Start	Manual Start	
Halogen 1-Bulb	LED with Accent Light	LED with Accent Light	
10.2 cm (4 in.) Low-Height	2.5 cm (1 in.) Mountain-Height	2.5 cm (1 in.) Mountain-Height	
Hand and Thumb Warmer, Tether Switch, Digital Gauge	12V Outlet, Goggle Holder, Hand and Thumb Warmers, Ice Scratchers, Lightweight Mountain Brake Disc, Sport Front Bumper, Tether Switch, Vertical Steering, Deluxe Digital Gauge	12V Outlet, Goggle Holder, Hand and Thumb Warmers, Ice Scratchers, Lightweight Mountain Brake Disc, Sport Front Bumper, Tether Switch, Vertical Steering, Deluxe Digital Gauge, Short Mountain Tunnel Cooler	

BESÖK EN ÅTERFÖRSÄLJARE NÄRA DIG



På arcticcat.se hittar du Sveriges alla återförsäljare av Arctic Cat snöskoter.

VÄLKOMMEN!

TECHNOLOGY

CROSSOVER











	RIOT X 8000	RIOT 8000	ZR 9000 THUNDERCAT EPS	ZR 8000 RR
KEY TECHNOLOGIES (*Optional)	ALPHA-ONE, ATAC, ADAPT	ADAPT	EPS, ATAC, ADAPT	ADAPT
COLOR OPTIONS				
STANDARD COLORS	Dynamic Charcoal/Fire Red, Orange	Dynamic Charcoal/Medium Green	Dynamic Charcoal	Medium Green
ENGINE				
ENGINE / TYPE / DISPLACEMENT / COOLING / CYLINDERS	8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder	8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder	9000 C-TEC4 / 4-Stroke / 998cc / Liquid / 3 Cylinder - Turbocharged	8000 C-TEC2 / 2-Stroke / 794cc / Liquid / 2 Cylinder
FUEL CAPACITY / OIL SYSTEM CAPACITY	44.3 l / 3.08 l (11.7 gal / 3.25 qt)	44.3 l / 3.08 l (11.7 gal / 3.25 qt)	37.5 l /3.6 l (9.9 gal / 3.8 qt)	44.3 l / 3.08 l (11.7 gal / 3.25 qt)
DRIVE CLUTCH	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT
DRIVEN CLUTCH	ADAPT CVT	ADAPT CVT	ADAPT CVT	ADAPT CVT
SUSPENSION				
FRONT SUSPENSION	Arctic Mountain Suspension (AMS)	Arctic Race Suspension (ARS) II	Arctic Race Suspension (ARS) II	Arctic Race Suspension (ARS) II
REAR SUSPENSION	ALPHA-ONE Rear Suspension	CROSS-ACTION with 3 Wheel Rear Axle Assembly, Torque-Sensing Link Rear Arm and Adjustable Torsion Springs.	SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm and Adjustable Torsion Springs.	SLIDE-ACTION with 3 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm and Adjustable Torsion Springs
SKI SHOCKS	FOX 1.5 ZERO QS3 Coil-Over or FOX 1.5 ZERO iQS Coil-Over	FOX 1.5 ZERO QS3	FOX 1.5 ZERO iQS	FOX 1.5 ZERO QS3R KASHIMA
FRONT TRACK SHOCK	FOX 1.5 ZERO QS3 Coil-Over	Arctic Cat IFP 1.5	Arctic Cat IFP 1.5	FOX 1.5 ZERO QS3 KASHIMA
REAR TRACK SHOCK	FOX 1.5 ZERO QSL Coil-Over or FOX 1.5 ZERO iQSL Coil-Over	FOX 2.0 ZERO QS3	FOX 2.0 ZERO iQS	FOX 2.0 ZERO QS3R KASHIMA
CHASSIS & TRACK				
CHASSIS OVERALL LENGTH / WIDTH / HEIGHT	333 cm / 118-123 cm / 124 cm (131 in. / 46.5-48.5 in. / 49 in.)	335 cm / 124-124 cm / 122 cm (132 in. / 48-49 in. / 48 in.)	318 cm / 122-124 cm / 132 cm (125 in. / 48-49 in. / 52 in.)	318 cm / 122-124 cm / 122 cm (125 in. / 48-49 in. / 48 in.)
TRACK TYPE	Power Claw	Cobra	Back Country	Back Country
TRACK WIDTH / LENGTH / LUG	38 cm / 371 cm / 6.6 cm (15 in. / 146 in. / 2.60 in.)	38 cm / 371 cm / 5.1 cm (15 in. / 146 in. / 1.35 or 1.60)	38 cm / 348 cm / 4.4 cm (15 in. / 137 in. / 1.75 in.)	38 cm / 348 cm / 4.4 cm (15 in. / 137 in. / 1.75 in.)
SKI STANCE	100-105 cm (39.5-41.5 in.) Adjustable	105-110 cm (41.5-43.5 in. Adjustable)	107-109 cm (42-43 in.) Adjustable	107-109 cm (42-43 in.) Adjustable
FEATURES				
STARTER	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start	Push-Button Electric Start
HEADLIGHTS	LED with Accent Light	LED with Accent Light	LED with Accent Light	LED with Accent Light
WINDSHIELD	2.5 cm (1 in.) Mountain-Height	14 cm (5.5 in.) Race-Height	27.9 cm (11 in.) Mid-Height	14 cm (5.5 in.) Race-Height
STANDARD FEATURES	12V Outlet, Brake Disc, Goggle Holder, Hand and Thumb Warmers, Ice Scratchers, Sport Front Bumper, Vertical Steering, Tether Switch, Deluxe Digital Gauge	12V Outlet, Hand and Thumb Warmers, Ice Scratchers, Sport Front Bumper, Standard Brake Disc, Steering, Tether Switch, Deluxe Digital Gauge	12V Outlet, Goggle Holder, Handguards, Hand and Thumb Warmers, Heated Drivers Seat, Sport Front Bumper, Standard Brake Disc, Standard Steering, Tether Switch, Tunnel Flare, Deluxe Digital Gauge	12V Outlet, Handguards, Hand and Thumb Warmers, Sport Front Bumper, Lightweight Performance Brake Disc, Standard Steering, Tether Switch, Deluxe Digital Gauge





NORSEMAN X 8000	ZR 200 ES
ADAPT	
Dynamic Charcoal/Fire Red	Fire Red, Dynamic Charcoal/Medium Green
8000 Series / 2-Stroke / 794cc / Liquid / 2 Cylinder	200 / 4-Stroke / 192cc / Air / 1 Cylinder
44.3 l / 3.08 l (11.7 gal / 3.25 qt)	8.3 l / 3.08 l (2.2 gal / 0.6 qt)
ADAPT CVT	Arctic 13.3 cm (5.25 in.) Diameter (RPM Sensing)
ADAPT CVT	Arctic 17.1 cm (6.75 in.) Diameter v(Roller Cam)
Arctic Race Suspension (ARS)	Arctic Wishbone Suspension (AWS)
XTRA-ACTION Rear Suspension with adjustable torsion springs and Torque-Sensing Link rear arm	Slide-Rail, Adjustable Torsion Spring, Coil-Over Rear Shock
Arctic Cat IFP 1.5	Hydraulic Twin Tube
Arctic Cat IFP 1.5	N/A
Arctic Cat IFP 1.5	Hydraulic Twin Tube
335 cm / 116-131 cm / 132 cm (132 in. / 45.5-51.5 in. / 52 in.)	213 cm / 89-94 cm / 91 cm [84 in. / 35-37 in. / 36 in.]
Power Claw	Cobra
38 cm / 389 cm / 5.7 cm (15 in. / 153 in. / 2.25 in.)	25 cm / 2.36 cm / 2.5 cm (10 in. / 93 in. / 1 in.)
90-105 cm (35.5-41.5 in.) Adjustable	75-80 cm (29.5-31.5 in.) Adjustable
Push-Button Electric Start	Turn-key Electric Start
Dual Halogen 2-Bulb	Halogen 1-Bulb
35.5 cm (14 in.) Mid-Height	10.2 cm (4 in.) Low-Height
Hand and Thumb Warmers, Front Sport Bumper, Tow Hitch, Rear Rack, Tether Switch, 12V Outlet, Deluxe Digital Gauge	Brake Disc, Hand and Thumb Warmers, Steering, Tether Switch, Youth Front Bumper





- · · ·
- \wedge
- \wedge
- \wedge



Every Arctic Cat is designed in Minnesota and assembled

by American workers in the town of Thief River Falls.

That means your sled is built with pride,

right in the heart of snowmobiling country.

Snowmobiling is serious fun. Be sure to read and understand your owner's manual and please pay special attention to the safety instructions. Arctic Cat Inc. endorses and encourages the safe use of all snowmobiles. Be careful; you can get hurt. Wear an approved helmet and don't drink and ride. Be aware of natural hazards you may encounter, allow yourself plenty of room to safely stop your snowmobile under all conditions, and maintain your equipment. Your safety is in your hands, so take care. All scenes depicted or described in this brochure were performed by professional riders under carefully controlled conditions. Leave the fancy riding to the pros; they practice for years and train very hard to make it look easy. Never attempt to duplicate these maneuvers or encourage others to do so. We care about your safety and enjoyment of the sport. All materials and specifications are subject to change without notice. All specifications, competitive specifications, claims and information contained within are based on current knowledge and readily available printed material available as of January 1, 2019. All rights reserved. Cobra^M and RipsawTM are trademarks of Canso Inc. Diamond Direct DriveTM is a trademark of Black Diamond, Inc. FOX[®], FOX FLOAT[®] and FOX[®] ZERO are registered trademarks of FOX Racing Shox. TEAM[®] Rapid ResponseTM is a trademark of Stack Diamond, Inc. FOX[®], Arctic Cat[®], Arctic Mountain SuspensionTM, Arctic Race SuspensionTM, AscenderTM, Arctic Wishbone SuspensionTM, MeyTM, Bearcat[®], C-TEC2TM, C-TEC4TM, ATACTM, Mountain Cat[®], Prove ClawTM, ProClimbTM, SLIDE-ACTION Rear SuspensionTM, Son GrossTM, Team Arctic [®], Thordercat[®], Stode grossTM, Team Arctic [®], Thordercat[®], Torque-Sensing LinkTM and ZR[®] are trademarks of Arctic Cat Inc. The Arctic Cat Inc. ARCTIC CAT SONLINE 40. EVERYTHING FROM MACHINES ADD SPECS DOWN TO THE ACCESSORIES AND GEAR YOU NEED TO TAKE ON THE WORLD. Part #82655-63.

arcticcat.se