ZR R-XC



VEHICLE SPECS

ENGINE

| | ZR 600 R-XC | ZR 858 R-XC |
|-------------------------|--|--|
| Engine Type | 600, 2-Stroke | 600, 2-Stroke |
| Displacement ? | 599cc | 599cc |
| Cooling ? | Liquid | Liquid |
| Cylinders ? | 2 | 2 |
| Bore x Stroke 🥎 | 73.8 x 70 mm | 73.8 x 70 mm |
| Lubrication ? | Electronic Injection | Electronic Injection |
| Ignition | Digitally Controlled CDI | Digitally Controlled CDI |
| Engine Stator Output 🥎 | 270W@3000 RPM | 270W @ 3000 RPM |
| Fuel Delivery 🥎 | Dual Stage Injection | Dual Stage Injection |
| Exhaust | APV w/ Tuned Pipe, Pipe Sensor, Stainless Steel Manifold & Muffler | APV w/ Tuned Pipe, Pipe Sensor, Stainless Steel Manifold & Muffler |
| Fuel Capacity | 10.4 gal | 10.4 gal |
| Oil System Capacity | 3.00 qt | 3.00 qt |
| Coolant System Capacity | 5.4 qt | 5.4 qt |
| Minimum Octane ? | 91 | 91 |

POWERTRAIN

| | ZR 600 R-XC | ZR 858 R-XC |
|------------------------|---|---|
| Drive Clutch 🥎 | ADAPT | ADAPT |
| Driven Clutch ? | ADAPT | ADAPT |
| Drive System | AC Trail Belt Drive | AC Trail Belt Drive |
| Brakes | Stealth Hydraulic Master Cylinder w/ Race Caliper | Steatth Hydraulic Master Cylinder w/ Race Caliper |
| Clutch Calibration 🥎 | 0-5,000 ft | 0-5,000 ft |
| Gearing | 30/58 | 30/58 |
| Chain Pitch | Belt | Bett |
| Track Drive Sprocket 🥎 | 8 Tooth, 2.86 Pitch, Exvolute | 8 Tooth, 2.86 Pitch, Exvolute |
| Reverse | Push-Button Engine | Push-Button Engine |

SUSPENSION

| | ZR 600 R-XC | ZR 858 R-XC |
|------------------|---|---|
| Front Suspension | AWS 42 | AWS 42 |
| Ski Shocks | FOX QS3R | FOX QS3R |
| Sway Bar 🥎 | Standard | Standard |
| Front Travel | 8.2 in | 8.2 in |
| Rear Suspension | R-XC SLIDE-ACTION w/ 4 Wheel Rear Axte Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs | R-XC SLIDE-ACTION w/ 4 Wheel Rear Axle Assembly, Coupling Blocks, Torque-Sensing Link Rear Arm & Adjustable Torsion Springs |

| | ZR 600 R-XC | ZR 858 R-XC |
|-------------------|-------------------|-------------------|
| Front Track Shock | FOX 1.5 ZERO QS3 | FOX 1.5 ZERO QS3 |
| Rear Track Shock | FOX 2.0 ZERO QS3R | FOX 2.0 ZERO QS3R |
| Rear Travel | 13.5 in | 13.5 in |

DIMENSIONS

| | ZR 600 R-XC | ZR 858 R-XC |
|------------------------|---------------------------|---------------------------|
| Overall Chassis Length | 126 in | 126 in |
| Overall Chassis Width | 48-49 in | 48-49 in |
| Overall Chassis Height | 48 in | 48 in |
| Track Type | Cobra | Cobra |
| Track Width | 15 in | 15 in |
| Track Length | 137 in | 137 in |
| Lug | 1.35 in | 1.35 in |
| Pitch ? | 2.86 in | 2.86 in |
| Ski Stance | 41.5-42.5 in - Adjustable | 41.5-42.5 in - Adjustable |
| Ski Type/Width | Trail - 6 in | Trail - 6 in |
| Runner Type | Single Runner w/ Carbide | Single Runner w/ Carbide |

INSTRUMENTATION

| | ZR 600 R-XC | ZR 858 R-XC |
|-----------------|-------------------|-------------------|
| Type of Gauge | Sport | Sport |
| Speedometer | Digital | Digital |
| Tachometer 🥎 | Digital | Digital |
| Odometer | Digital | Digital |
| Fuel | Digital | Digital |
| Oil | LCD Icon | LCD Icon |
| Coolant | Digital Bar Graph | Digital Bar Graph |
| Clock | N/A | N/A |
| Battery Voltage | N/A | N/A |
| Altimeter | N/A | N/A |
| Hours | Digital | Digital |

FEATURES

| | ZR 600 R-XC | ZR 858 R-XC |
|----------------------|--|--|
| Color | Medium Green/Black | Medium Green/Black |
| Heat Exchanger 🥎 | Front/Long Tunnel | Front/Long Tunnel |
| Starter | Manual or Push-Button Electric Start | Manual or Push-Button Electric Start |
| Handlebars | Hooked | Hooked |
| Lighting | LED | LED |
| Seating | Trail | Trail |
| Standard Accessories | 12V Outlet, Sport Front Bumper, Hand & Thumb Warmers, Handguards, Race Brake Disc, Standard Steering, Tether Switch, Visor Plug-Ins | 12V Outlet, Sport Front Bumper, Hand & Thumb Warmers, Handguards, Race Brake Disc, Standard Steering, Tether Switch, Visor Plug-Ins |
| Windshield | 5.5 in Low Height | 5.5 in Low Height |